3M[™] 4400 Visitors Coat

The 3M[™] 4400 Visitor Coat is designed to help protect the wearer against non-hazardous dusts and light non-hazardous liquid splashes in parts of the body covered by the garment. It is made from the same fabric as the 3M[™] 4500 Coverall making it breathable and comfortable to wear for non-hazardous applications.

Key Features

- Includes internal pocket on the wearers left hand side (measuring 2 cm wide x 13cm high)
- · Elasticated wrists for a good fit
- · Front zip closing (single way) for convenience
- Low-linting material
- Breathable material to help reduce heat and build up and promote comfortable wear

Typical Applications

- General Maintenance
- Catering
- Electronics Manufacturing
- Laboratories

Approvals

This product is CE Category I for use in low risk applications. A risk assessment should be carried out by a trained safety professional to ensure that appropriate PPE and accessories are selected and worn correctly. For more information, please contact 3M.

Materials

Visitors Coat 45gsm Polypropylene

Zipper Metal / Nylon / Polyester Braid

Elastic Neoprene Rubber

Thread Polyester / Cotton

This product does not contain components made from natural rubber latex.

Sizing

An appropriate size garment should be selected to allow sufficient movement for the task whilst maintaining a secure fit.

	Height		Chest	
S	57 – 62 in	144 – 157 cm	28 - 32 in	71 – 81 cm
M	60 – 67 in	167 – 176 cm	32 – 36 in	81 - 91 cm
L	65 – 70 in	174 – 181 cm	36 – 38 in	91 – 97 cm
XL	68 – 73 in	179 – 187 cm	38 - 40 in	96 - 101 cm
XXL	71 – 75 in	186 – 194 cm	40 - 43 in	101 – 109 cm
3XL	73 – 77 in	194 – 200 cm	43 –46 in	109 – 1117 cm
4XL	74 – 78 in	200 – 206 cm	46 – 52 in	117– 132 cm



3M Safety Solutions

3M United Kingdom 3M Centre, Cain Road, Bracknell Berkshire RG12 8HT Tel: 0870 60 800 60 www.3M.co.uk/ohes 3M Ireland Limited The Iveagh Building The Park, Carrickmines Dublin 18 Tel: 1 800 320 500

Storage and Disposal

- Store in dry, clean conditions in original packaging, away from direct sunlight, sources of high temperature, and solvent vapours
- \bullet Store within the temperature range -20°C to +25°C (-4°F to +68°F) and with relative humidity below 80%
- Expected shelf life is three years from date of manufacture when stored as stated
- Replace garments if damaged, heavily contaminated or in accordance with local work practice or regulations
- Handle and dispose of contaminated garments with care and in accordance with applicable regulations

Limited Use



Do not wash



Do not dry clean



Do not bleach



Flammable — keep away from sparks or flames



Do not iron



Single Use - do not re-use



Do not tumble dry

Warnings and Limitations

Before use be sure that the product is suitable for the application and fitted correctly. Product must never be altered or modified.

Do not use for:

- Contact with heavy oils, sparks or flame, or combustible liquids;
- Environments with high mechanical risks (abrasions, tears, cuts);
- Protection against hazardous substances
- · Environments with conditions of excessive heat.

For more information on 3M products and services please contact 3M.

Important Notice

This guide is only an outline. Before using any protective clothing or accessories, the wearer must read and understand the user information for each product. Specific country legislation should be observed. If in doubt, contact a safety professional. Selection of the most appropriate PPE and accessories will depend on the particular situation and should only be made by a competent person knowledgeable of the actual working conditions and the limitations of PPE and accessories. Final determination as to the suitability of these products for a particular situation is the employer's responsibility. This information is subject to revision at any time. If you have questions contact 3M Technical Service.

3M Health & Safety Helpline

0870 60 800 60 (UK) 1 800 320 500 (Ireland)

CH4400DS Is