

# Product information

## ROTARY HAMMER SDS MAX



Satisfying the professional's needs

### HR4013C

Impact energy	8.0 J
Max in concrete	40 mm
Impacts per minute	1450 - 2900 ipm
Input Wattage	1000 w
Vibration K factor	1.5 m/sec <sup>2</sup>
No Load Speed	250 - 500 rpm
Vibration: Chiselling	4.5 m/sec <sup>2</sup>
Vibration: Hammer Drilling	5 m/sec <sup>2</sup>
Net weight with pipes	6.8 kg



**STANDARD EQUIPMENT:** Side handle, Depth stop, Bit grease, Carry case

- One touch sliding chuck for easy bit installation and removal.
- Easy to operate operation-mode change lever. Located on the top of the motor housing for reduced possibility of breakage.
- "Soft no load" function automatically reduces the motor speed during idling to suppress the vibration of the machine body.
- Unrivalled low level of vibration aided by vibration absorbing housing.
- LED service light indicates when to replace carbon brush.
- In hammering mode, on/off switch is switchable between two switches to meet your application: For Continuous or Intermittent chiseling applications.

Details correct as of: 20-6-2017

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

[www.makita.com](http://www.makita.com)