

# **Product data sheet**



Straight Grinder

## **GGS 28 C Professional**

The handy tool for universal grinding work

#### The most important data

Rated power input	600 W
No-load speed	30.000 rpm
Bit holder	Collets up to 8 mm diameter

#### **Technical Data**

Performance data		
No-load speed	30.000 rpm	
Bit holder	Collets up to 8 mm diameter	
Spindle collar diameter	43 mm	
Max. collet diameter	8 mm	
Max. grinding tool diameter	50 mm	
Spanner size of locking nut	19 mm²	
Spanner size of grinding spindle	19 mm²	
Switch	2-way	
Battery and power		
Rated power input	600 W	
Power output	350 W	
Size and weight		
Weight	1,4 kg	

#### Noise/vibration information

Surface grinding up to diameter of 25		
Vibration emission value ah	3,0 m/s <sup>2</sup>	
Uncertainty K	1,5 m/s <sup>2</sup>	
Surface grinding up to diameter of 50		
Vibration emission value ah	8,0 m/s <sup>2</sup>	
Uncertainty K	1,5 m/s²	
Noise		
Sound pressure level	89 dB(A)	
Sound power level	100 dB(A)	
Uncertainty K	3 dB	



#### Power tools for trade & industry

### **Advantages**

- Compact, ergonomic shape for versatile grinding work
- Powerful 600 watt motor with soft start for fast work progress
- KickBack Stop: detects when the tool is jammed and shuts it down immediately
- Little servicing required due to significantly improved carbon brushes
- Constant Electronic for constant speed, also under heavy load
- New clamping system for a secure fit of the grinding stones to ensure precise work











