

HD18 HX-O | M18™ Heavy Duty 4-mode SDS hammer drill

Article: 4933408320



- High powered motor gives corded tool performance.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM-ION™ battery pack delivers up to 2x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Powerful hammer mechanism: delivers 2.4 J (EPTA) of impact energy.

HD18 HX-O	
Sound pressure level (dB(A))	88
Sound pressure level uncertainty [dB(A)]	3
Sound power level [dB(A)]	99
Sound power level uncertainty [dB(A)]	3
Vibration chiselling uncertainty [m/s²]	1.5
Vibration drilling into concrete [m/s²]	12.2
Vibration drilling into concrete uncertainty [m/s²]	1.5
Voltage (V)	18
Battery pack capacity (Ah)	-
Battery type	Li-ion
Max. percussion rate (bpm)	4200
Optimised drilling capacity in concrete [mm]	ø 6 - 18
Supplied in	-
Charger supplied	-
No. of batteries supplied	0
Vibration drilling (m/s²)	12.2
Vibration chiseling (m/s²)	7.4
Article Number	4933408320
Weight with battery pack (kg)	-
Weight (kg)	3.0
Max drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. drilling concrete (mm)	24
Blow energy [EPTA][J]	2.4