




## HDS 10/20-4 M

Medium class hot water high-pressure cleaner with a host of user-friendly features. With 3-phase power supply for higher performance.



### 1 Efficiency

- In the Eco setting the unit operates in the most economical temperature range (60°C) with full water flow.
- Burner cycles are optimised to reduce fuel consumption by up to 20% compared to full-load operation.

### 2 Maximum efficiency

- Highly efficient burner technology.
- 4-pole electric motor with 3 piston axial pump.

### 3 Operational reliability

- The large, integrated fine-mesh water filter reliably protects the high-pressure pump against dirt particles.
- An integrated exhaust gas thermostat switches off the drive motor if the exhaust gas temperature exceeds 300°C.

### 4 Storage

- Safe and ample storage for protective gear, accessories and cleaning agents.
- Storage hooks for power cord and high-pressure hose.



## HDS 10/20-4 M

- Economical ecoefficiency mode
- Two detergent tanks
- Three-phase motor: water-cooled

### Technical data

|                        |               |                   |
|------------------------|---------------|-------------------|
| Order Number           | 1.071-902.0   |                   |
| EAN code               | 4054278140230 |                   |
| Current type           | Ph / V / Hz   | 3 / 420 / 50      |
| Flow rate              | l/h           | 500-1000          |
| Pressure               | bar / MPa     | 30-200 / 3-20     |
| Max. temperature       | °C            | 80 / 155          |
| Power rating           | kW            | 7,8               |
| Consumption fuel oil   | kg/h          | 6,4               |
| Fuel tank              | l             | 25                |
| Weight                 | kg            | 163               |
| Dimensions (L x W x H) | mm            | 1330 x 750 x 1060 |

### Equipment

|  |                     |                        |   |
|--|---------------------|------------------------|---|
| Trigger gun  | EASY!Force Advanced | Two detergent tanks    | ■ |
| High-pressure hose   | m                   | Dry running protection | ■ |
| Spray lance  | mm                  |                        |   |
| Power nozzle   | ■                   |                        |   |
| Servo Control  | -                   |                        |   |
| ANTI!Twist   | -                   |                        |   |
| Tanks for detergent, scale inhibitor and fuel can be filled from outside | ■                   |                        |   |
| Control panel with indicator lamps                                       | ■                   |                        |   |
| Pressure switch control  | -                   |                        |   |
| Pole reversing plug (three-phase)  | ■                   |                        |   |
| Electronic service control with LED display                              | ■                   |                        |   |

■ Included in delivery.