874 Best® Butyl II





RECOMMENDED FOR THESE RISKS: Chemicals RECOMMENDED FOR THESE LINES OF WORK: Chemical industry / Acid components Police & Army Chemical industry / Acetone and Ketone components

Unsupported Butyl coating

DESCRIPTION

- · Fully coated
- Rolled cuff
- Standard finish
- Without special treatment
- Anatomical shape
- · Available by individual pair in polybag with eyelet

BENEFITS

- A thin, light glove with a "second skin" feel
- Protects the hand from a wide array of chemical hazards (more information on www.chemrest.com)
- · Impermeable for working in damp or greasy environments
- · Cuff prevents dirt from entering the glove
- · Lower allergy risks
- · Designed for easy movement and continuous wear
- · Packaging that helps finding the right model in displays
- · Wrist well protected
- Low-soil colour

AVAILABLE SIZES	8/M•9/L•10/XL•11/XXL
LENGTH Dependent on size, in mm (flat)	350
PACKAGING Pairs or pieces per pack/box	1/12
COLOUR OF SUPPORT/COATING	Black
THICKNESS in mm	0.35

RECOMMENDATIONS FOR USE

- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary
- Do not wear gloves when there is a risk of entanglement by moving parts of machines.
- · Potential allergens: thiazoles and thiurames



Globus Building 38 Wheel Forge Way Trafford Park, Manchester M17 1EH **Tel:** 0161 877 4747 **Fax:** 0161 877 4746 www.globus.co.uk
 Cat. III
 EN388 - 1994
 ABRASION CUTTING 0 1234
 EN 374-2 - 1994
 EN 374-3 - 1994
 HYDROCHLORIC ACID 36%
 KEROSENE 0 12 3 4 5 6

 TEARING 0 12 3 4
 PUNCTURE 0 12 3 4
 PUNCTURE 0 12 3 4
 PUNCTURE 0 12 3 4
 EN 374-2 - 1994
 EN 374-3 - 1994
 HYDROCHLORIC ACID 36%
 KEROSENE 0 12 3 4 5 6

 TEARING 0 12 3 4
 PUNCTURE 0 12 3 4
 PUNCTURE 0 12 3 4
 METHANOL 0 12 3 4 5 6
 CAUSTIC SODA 4%





EC compliance certificate delivered by the notified body 0516 STFI Germany - Postfach 1325 - D-09072 Chemnitz - Germany The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.