

DGA463Z

Battery Type	Lithium-ion
Body only machine	1
Voltage	18 v
Bore Diameter	22.23 mm
Max Wheel Thickness	7.2 mm
Noise sound pressure	79 dB(A)
Noise K factor	3 dB(A)
Max Wheel Diameter	115 mm
No Load Speed	3,000 - 8,500 rpm
Vibration K factor	1.5 m/sec ²
Vibration: Surface Grinding	6.5 m/sec ²
Vibration: Disc Sanding	2.5 m/sec ²
Net weight	2.3 - 3.0 kg



STANDARD EQUIPMENT: Lock nut wrench, Side handle, Grinding wheel

- Brushless motor
- Variable speed control dial.
- Anti-restart function.
- Electric brake
- On/off slide switch.
- Electronic current limiter for overload protection.
- Battery fuel gauge
- Ergonomic soft grip
- Automatic Torque Drive Technology: Automatically changes the cutting speed according to load condition for an optimum operation
- Active Feedback Sensing Technology (AFT): Shuts down the tool to protect the user if the rotation speed suddenly slows down
- Removable dust covers
- Lock-on function

Details correct as of: 13-3-2018

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.