



## Product data sheet



Charger

### GAL 3680 CV Professional

The multi-volt quick charger for all Li-Ion batteries from 14.4 to 36 volts

#### The most important data

Charge current	8,0 A
Battery charging voltage	14,4 – 36 V
Weight	900 g

#### Technical Data

Performance data	
Battery charging voltage	14,4 – 36 V
Charge current	8,0 A
Charg. time at bat. cap. 1.5 Ah (80%/100%) approx.	10/25 mins
Charg. time at bat. cap. 2.0 Ah (80%/100%) approx.	15/30 mins
Charg. time at bat. cap. 2.5 Ah (80%/100%) approx.	15 mins
Charg. time at bat. cap. 3.0 Ah (80%/100%) approx.	20/35 mins
Charg. time at bat. cap. 4.0 Ah (80%/100%) approx.	25/35 mins
Charg. time at bat. cap. 5.0 Ah (80%/100%) approx.	30/45 mins
Charg. time at bat. cap. 6.0 Ah (80%/100%) approx.	35/55 mins
Charg. time at bat. cap. 6.3 Ah (80%/100%) approx.	41/55 mins
Size (L x W x H)	196 x 128 x 82 mm
Size and weight	
Weight	900 g



Power tools for trade & industry

---

**Advantages**

- 100% faster charging of the batteries (compared to AL 3640 CV)
- Quick-charge mode: 4.0 Ah battery is ready to use with 80% of its capacity after only 25 mins
- Active Air Cooling for longer lifetime of the batteries
- Convenient cord wrap
- Very compact

