

HD18 HX-402C | M18™ Heavy Duty 4-mode SDS hammer drill

Article: 4933441283



- High powered motor gives corded tool performance.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM-ION[™] battery pack delivers up to 2x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- REDLINK[™] overload protection electronics in tool and battery pack deliver best in class system durability.
- Powerful hammer mechanism: delivers 2.4 J (EPTA) of impact energy.

| | HD18 HX-402C |
|---|--------------|
| Sound pressure level (dB(A)) | 88 |
| Sound pressure level uncertainty [dB[A]] | 3 |
| Sound power level [dB[A]] | 99 |
| Sound power level uncertainty [dB[A]] | 3 |
| Vibration chiselling uncertainty [m s ²] | 1.5 |
| Vibration drilling into concrete [m s ²] | 12.2 |
| Vibration drilling into concrete uncertainty [m s ²] | 1.5 |
| Voltage (V) | 18 |
| Battery pack capacity (Ah) | 4.0 |
| Battery type | Li-ion |
| Max. percussion rate (bpm) | 4200 |
| Optimised drilling capacity in concrete [mm] | ø 6 - 18 |
| Supplied in | Kitbox |
| Charger supplied | 80 min |
| No. of batteries supplied | 2 |
| Vibration drilling (m/s ²) | 12.2 |
| Vibration chiseling (m/s ²) | 7.4 |
| Article Number | 4933441283 |
| Weight with battery pack (kg) | 3.7 |
| Max drilling steel (mm) | 13 |
| Max. drilling wood (mm) | 30 |
| Max. drilling concrete (mm) | 24 |
| Blow energy [EPTA][J] | 2.4 |

