

# Product information

## Circular Saw 190mm



### HS7601J

Depth of Cut @ 90°	66 mm
Blade Diameter	190 mm
Depth of Cut @ 45°	46 mm
Bore Diameter	30 mm
Noise sound pressure	87 dB(A)
Noise sound power	98 dB(A)
Noise K factor	3 dB(A)
Input Wattage	1200 w
No Load Speed	5200 rpm
Vibration K factor	1.5 m/sec <sup>2</sup>
Vibration: Cutting Wood	2.5 m/sec <sup>2</sup>
Net weight	4.0 kg
Supplied with MAKPAC Case	1



**STANDARD EQUIPMENT:** 821552-6 MAKPAC CONNECTOR CASE (TYPE 4), 838108-8 Makpac Machine Inlay, TCT saw blade, Hex wrench, Rip fence (Guide rule), Dust nozzle

- Double Insulation
- Compact and lightweight design
- New Aesthetic Design
- Compatible with Guide Rail
- Rear dust exhaust port
- Connectable to dust extractor
- Rear angular guide for smooth and precise adjustment of bevel angle
- Single action lever for quick adjustment of cutting depth
- Ergonomic soft grip
- Flat motor housing end
- Aluminium die-cast safety cover
- Aluminium base plate

Details correct as of: 29-6-2017

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

[www.makitauk.com](http://www.makitauk.com)