



IV 60/24-2 W

The IV 60/24-2W is a very robust industrial vacuum cleaner used for dry or wet applications. The construction type and the various accessories available make it highly mobile, being used in different sites of the factory and practical for different cleaning tasks. The model is not recommended to be used for continuous duty (3-shift-operation) because of the motor type embedded in it. It will be operated with 220-240 V, 50-60 Hz. Depending on the operation, container (dry) part-no. 6.394-523.0 or container (wet) part-no. 6.394-528.0 need to be ordered separately.



1 2 blower motors

Powerful cleaning performance with 2 blowers. Electronically controlled motors avoid high starting currents.

3 Convenient storage area for accessories on the machine's chassis

Large accessory basket on the machine chassis offers a convenient storage space for nozzles, bends and other parts.

2 Manual filter vibration for low operating costs

■ The manual filter vibration increases the working time of the permanent filter, thereby reducing the maintenance effort.

4 Resilient and versatile

The extensive accessory line provides for ergonomic and economical cleaning solutions for numerous applications.

TECHNICAL DATA AND EQUIPMENT





IV 60/24-2 W

- Anti-static equipment
- Filter status indicator
- Robust wheels and castors

		RODUST WHEELS AND CASTOTS
Technical data		
Order no.		1.573-200.0
EAN code		4039784731110
Rated input power during operation	kW	2.4
Air flow rate	$l/s / m^3/h$	112 / 403
Vacuum	mbar / kPa	235 / 23.5
Container capacity	I	60
Filter area	m²	2.3
Main filter dust class		M
Sound pressure level	dB(A)	73
Nominal diameter of connection		ID 51
Weight	kg	70
Nominal diameter of accessory		ID 51
Dimensions (L × W × H)	mm	870 × 640 × 1410
Equipment	,	
Assessation in seems of delivery		No

Equipinent	
Accessories in scope of delivery	No No
Container in scope of delivery	NO NO
Container for wet vacuuming	6.394-822.0
Container for dry applications	6.394-821.0
Filter cleaning	Manual