

Product information

260mm Slide Compound Mitre Saw



Satisfying the professional's needs

LS1019L

Blade Diameter	260 mm
Max mitre range	60 - 60 °
Max mitre cut at 90°	68 x 310 mm
Bore Diameter	30 mm
Max bevel range	48 - 48 °
Noise sound pressure	91 dB(A)
Noise sound power	101 dB(A)
Noise K factor	3 dB(A)
Input Wattage	1510 w
No Load Speed	3200 rpm
Vibration K factor	1.5 m/sec ²
Vibration no load	2.5 m/sec ²
Net weight	26.3 kg



STANDARD EQUIPMENT: TCT saw blade, Dust bag, Triangular rule, Vertical vice, Hex wrench

- Built in laser guide.
- Motor head slides on fixed pipes without extending machine at rear end, so the machine can be placed close to wall.
- Front knob for easy bevel adjustment
- Holders to support a wide workpiece
- Easy-to-operate mitre angle lock
- One-touch sliding lock
- Large turn base
- Connects to dust extractor
- Electric brake
- Soft start
- Constant speed control
- Double Insulation

Details correct as of: 16-8-2018

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

www.makitauk.com