# WorkGuard™ 43-216

# TECHNICAL DATASHEET

# **Special Purpose**

Print date 13-10-2016

#### **Glove material**

- Leather (1.2 split cowhide A/B grade) (Liner material)
- Kevlar® seams (Liner material)
- Cotton Jersey (Liner material)

#### **Possible Harmful ingredients**

#### Sensitizers

No sensitizers

#### Reach Regulation 1907/2006

For more information, please consult the REACH statement on the Ansell website

#### **Properties**

Good abrasion and excellent tear resistance

#### **EN Test Data**

а	b	С	d	е	f	
3	2	4	3			

#### Flammability:

EN388:2013

Performance level 4 After flame time <2s, After glow time <5s

### Contact heat resistance:

Performance level 1 Contact temperature 100°C >15s

### Convective heat resistance:

Performance level 3 Heat Transfer Index >10s

#### Radiant heat resistance:

Performance level X (test not applicable)

# Resistance to small projections of molten metal:

Performance level 4 >35 droplets

# Resistance to large quantities of molten metal:

Performance level X (test not applicable)

# **European conformity**

Gloves conform to the requirements of the European Directive 89/686/EEC and to the European standards EN 420:2003 + A1:2009 and EN 388:2003.EN 407:2004

They are categorised in "Complex Design" (= Protection against mortal risks).

EC-Type Examination Certificate and EC-quality control for the final product by

Centexbel

Technologiepark 7 B-9052 Zwijnaarde

#### **Application - Limitations of use**

Mechanical & Do not use in heavy-duty cut applications
The glove is not liquidproof, hence is not to be used against

#### Storage

chemicals

Keep away from sources of ozone or ignition. Keep out of direct sunlight; store in a cool and dry place.

Construction	Liner material	Cuff style	Colour	EN Size	Length mm	Packaging
Cut & sewn	Leather (1.2 split cowhide A/B grade) Kevlar® seams Cotton Jersey	Gauntlet	Yellow	9, 10, 11	370-415	6 pairs in a bag; 6 bags in a carton





