

Product data sheet

H3.2



Key selling points

- **From the homogeneous circle of close range lighting (defocused) to a sharply bundled long-distance beam (focused)** – The patented³ Advanced Focus System with reflector lens enables efficient, tailored lighting
- **Excellent Ledlenser lighting quality** – Brightness, beam distance and lighting duration are ideally coordinated for the energy source
- **Optimized operational time** – Up to 60 hours¹ in the lowest setting
- **Solid light output** – Up to 100 meters¹ beam distance with up to 60 lumen¹ of luminous flux
- **Comfortable, lightweight headlamp** – Weighs just 133grams with batteries
- **Convenient and ergonomic** – Optimum weight distribution
- **Continuous dimming down to 5 lumen** – Can be adjusted using the regulator on the battery box
- **Gentle on the neck muscles** – Always the optimum light angle thanks to the 75° swivel rotation of the lamp head
- **Battery operated** – Three AAA alkaline batteries (micro, 1.2 V) are used

Specifications



Technical Data	
Head diameter [mm]	28
Weight incl. batteries [g]	133
Weight without batteries [g]	99
Focus Function	yes
Head material	Aluminum alloy
Housing material	Other plastics
Optic	Lense PMMA
Headband material	Elastic fabric
Headband type	Side headband
Head movement type	Stepped movement
Head movement angle [°]	75°
Headband specifications	Washable, elastic, detachable

Power supply	
Power source type	Battery
Battery quantity	3
Battery Technology	Micro (AAA) 1.5V
Battery Type	Alkaline
Total battery voltage [V]	4.5
Total battery capacity [mAh]	1250
Total battery energy ² [Wh]	5.63
Rechargeable	no
Charging time [min]	-
Charging technology	-
Energy Modes	Energy Saving
Energy Status Indicator	-
Usable batteries	AAA NiMH 1.2V AAA 1.5V

Further Technical Specifications	
IP class	IPX4
Drop test (drop height) [m]	1
IK Code [J]	-
Maximum operating depth [m]	-
ATEX Zone	-
Working temperature range [°C]	-20 to 40°C

Light Function

Low Power, Power

Light Source

Amount LEDs	1
LED type	Power LED
Color	White
Color temperature [K]	6.000 to 8.000
Color rendering index (CRI)	75

Light values

	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]	-	120	-	5
Beam distance ¹ [m]	-	100	-	20
Run time ¹ [h]	-	6	-	60

Switch

Front Switch

Features

Dimmable


Technologies

Advanced Focus System, Rapid Focus

Award logos



Logos / Icons



Packing and logistics



Packaging Information	
Type of packaging	Box
Scope of delivery	1 set of batteries, warnings, mini catalog, warranty card, quick user guide
Item No.	500767
Customs tariff number	85131000

Single Package	
Dimensions L x W x H [mm]	100 x 80 x 80
Gross weight [g]	208
Net weight [g]	75
GTIN-13	4058205000666

Inner carton	
Unit	6
Dimensions L x W x H [mm]	255 x 210 x 900
Gross weight [g]	1467
Net weight [g]	1250
GTIN-13	4058205000758

export carton	
Unit	36
Dimensions L x W x H [mm]	445 x 295 x 315
Gross weight [kg]	10
Net weight [kg]	8.8
GTIN-13	4058205000840



Packaging Information	
Type of packaging	Test It Blister
Scope of delivery	mini catalog, quick user guide, warranty card, warnings, 2 sets of batteries
Item No.	500768
Customs tariff number	85131000
	24.90

Single Package	
Dimensions L x W x H [mm]	236 x 205 x 760
Gross weight [g]	283.3
Net weight [g]	116.3
GTIN-13	4058205000673

Inner carton	
Unit	6
Dimensions L x W x H [mm]	510 x 213 x 125
Gross weight [g]	1950
Net weight [g]	1700
GTIN-13	4058205000765

export carton	
Unit	24
Dimensions L x W x H [mm]	530 x 450 x 280
Gross weight [kg]	9
Net weight [kg]	7.8
GTIN-13	4058205000857

Accessories

Item No.	Product name
-	-